

Autolite® Spark Plug Heat Range Chart

Tableau des températures des bougies Autolite®

Tabla de grados térmicos de bujías Autolite®

				A	B	C	D	E	F	G	H	I	J
	THREAD SIZE & REACH	HEX	HEAT RANGE	STANDARD (NON-RESISTOR)	STANDARD (RESISTOR)	POWER TIP (NON-RESISTOR)	POWER TIP (RESISTOR)	PLATINUM	DOUBLE PLATINUM	XTREME PERFORMANCE	PREMIUM SMALL ENGINE	SHIELDED (RESISTOR)	SURFACE GAP
1	10mm 1/4"	5/8"	HOT	3136									
			COLD										
2	10mm 1/2"	5/8"	HOT	4194							XST5438 ²⁴⁰⁰ , 2456, 7734, 7737		
			COLD										
3	10mm 3/4"	5/8"	HOT		4303						XS4303 ^{2399,7735}		
			COLD		4302						XS4302 ^{2399,7735}		
4	12mm 1/2"	11/16"	HOT	4173									
			COLD										
5	12mm 3/4"	11/16"	HOT				4164				XS4164 ²³⁹⁹ , 2400, 7735		
							4163				XS4163 ²³⁹⁹ , 2400, 7735		
			COLD	4132			4162				XS4162 ²³⁹⁹ , 2400, 7735		
6	14mm (Tapered Seat) .332"	5/8"	HOT	2956 ²⁴¹²							XST2956 ²⁴⁰⁰ , 2412, 2456, 7734,		
			COLD	2954 ²⁴¹²		2554 ²⁴¹²					XST2554 ²⁴⁰⁰ , 2412, 2456, 7734/ XST2954 ²⁴⁰⁰ , 2412, 2456, 7734		
7	14mm 3/8"	13/16"	HOT	458 ²⁴⁰¹ /258 ²³⁹⁸	308						XST458 ²⁴⁰⁰ , 2458, 7734/ XST258 ²³⁹⁸ , 2400, 2458, 7734	2247 ^{2399,7806}	
					306							2246 ²³⁹⁹	
				295/456 ²⁴⁰¹			847 ²⁰⁷³	AP847 ²⁰⁷³	APP847 ²⁰⁷³			2245 ^{2399, 7806}	
				255 ²³⁹⁸			86	AP86			XST255 ²³⁹⁸ , 2400, 7734	2244 ²³⁹⁹	
						4275	85	AP85			XS85 ²⁴⁰⁰ , 2399, 7735/ XST2976 ²³⁹⁸ , 2400, 7734	2243 ^{2399, 7806}	
					303	2976 ²³⁹⁸		AP303				2242 ²³⁹⁹	
				254 ²³⁹⁸							XST254 ²³⁹⁸ , 2400, 7734		
				353		2974 ²³⁹⁸					XST2974 ²³⁹⁸ , 2400, 7734,		
8	14mm 7/16"	13/16"	HOT			437							
			COLD	216/4316								2327 ²³⁹⁹	
9	14mm 1/2"	13/16"	HOT									2407 ²³⁹⁹ , 2400, 7806	
				2656	425	275		AP425 ²⁴¹⁷			XS2666 ²³⁹⁹ , 7735	2285 ²³⁹⁹	
						4114						2344 ^{2399, 7806} / 2384 ^{2399, 7806}	
				414									
				4093			4123				XS4093 ⁷⁷³⁵		2852 ²⁴⁵⁶
				4092							XS4092 ⁷⁷³⁵		2872 ^{2403, 2456}
			COLD	411, 2634 ²⁴⁰²							XS2644 ²³⁹⁹ , 7735		2892 ^{2397, 2456}

Se reporter à l'index pour les remarques en français en bas de page. Ver el índice para las páginas de notas de pie de página en español.

²⁰⁷³ .060" Gap. ²³⁹⁷ Series air gap. ²³⁹⁸ Bantam plug with 3/4" hex. ²³⁹⁹ Resistor. ²⁴⁰⁰ Power tip. ²⁴⁰¹ Special lawnmower plug. ²⁴⁰² .040" gap.

²⁴¹² Bantam spark plug. ²⁴¹⁷ Standard tip. ²⁴⁵⁶ Non-resistor. ²⁴⁵⁸ Bantam plug with .332" reach. ⁷⁷³⁴ Xtreme Start. ⁷⁷³⁵ Xtreme Sport. ⁷⁷³⁷ Tapered seat.

⁷⁸⁰⁶ Inductive suppressor.

Autolite® Spark Plug Heat Range Chart

Tableau des températures des bougies Autolite®

Tabla de grados térmicos de bujías Autolite®

	THREAD SIZE & REACH	HEX	HEAT RANGE	A	B	C	D	E	F	G	H	I	J
				STANDARD (NON-RESISTOR)	STANDARD (RESISTOR)	POWER TIP (NON-RESISTOR)	POWER TIP (RESISTOR)	PLATINUM	DOUBLE PLATINUM	XTREME PERFORMANCE	PREMIUM SMALL ENGINE	SHIELDED (RESISTOR)	SURFACE GAP
11	14mm 3/4"	5/8"	HOT				3926		APP3926		XST3926 ²³⁹⁹ , 2400, 7734		
							985 ²⁴⁰⁴	AP985 ²⁴⁰⁴	APP985 ²⁴⁰⁴	XP985 ²⁴⁰⁴	XS985 ²³⁹⁹ , 2404, 7735		
							3924/ 5184 ²⁰⁷³ / 5224 ²⁴⁰⁵	AP3924 AP5184 ²⁰⁷³ AP5405 ²⁴⁵⁹ AP5224 ²⁴⁰⁵	APP3924 APP5224 ²⁴⁰⁵	XP3924 XP5405 ²⁴⁵⁹ XP5224 ²⁴⁰⁵	XST3924 ²³⁹⁹ , 7734/XS3924 2399,7735/ XS5224 ²³⁹⁹ , 2405, 7735		
							3923 5503 ²⁴⁵⁹	AP3923 AP5503 ²⁴⁵⁹	APP3923 APP5503 ²⁴⁵⁹	XP3923 XP5503 ²⁴⁵⁹	XS3923 ²³⁹⁹ , 7735		
							3922						
12	14mm 3/4"	13/16"	HOT				4345 ²⁴⁰⁶						
							66 646 ²⁰⁷³	AP66 AP646 ²⁰⁷³	APP66 APP646 ²⁰⁷³	XP646 ²⁰⁷³			
					405		65/925 ²⁴⁰⁶ 4265	AP65	APP65		XST4265 ²³⁹⁹ , 2400, 7734/ XS65 ²³⁹⁹ , 2400, 7735		
				4056	404		64 2744 ²⁴⁰⁵	AP64 AP2744 ²⁴⁰⁵ AP404 ²⁴¹⁷	APP64	XP64		2304 ²³⁹⁹ , 7806	
							63/4263	AP63	APP63	XP63	XS63 ²³⁹⁹ , 2400, 7735		
				4055	403			AP403			XST4055 2456, 7734		
						4252	62	AP62			XS62 ²³⁹⁹ , 2400, 7735		
					2526 ²⁴⁰⁷ 2626 ²⁴⁰⁷	4251					XS61 ²³⁹⁹ , 2400, 7735		
				4054							XS4064 ²³⁹⁹ , 2400, 7735		
					4063						XS4063 ²³⁹⁹ , 2400, 7735		
					4062						XS4062 ²³⁹⁹ , 2400, 7735		
				COLD	4051								
13	14mm (Tapered Seat) .460"	5/8"	HOT		147/687 ²⁰⁷³								
							26 666 ²⁰⁷³	AP26 AP666 ²⁰⁷³	APP26 APP666 ²⁰⁷³	XP26			
					145/685 ²⁰⁷³		25 665 ²⁰⁷³ 5285 ²⁴¹⁰	AP25 AP665 ²⁰⁷³ AP145 ²⁴¹⁷	APP25 APP145 ²⁴¹⁷	XP25			
							24 664 ²⁰⁷³	AP24 AP664 ²⁰⁷³	APP24	XP24			
					144								
14	14mm (Tapered Seat) .708" Full Thread	5/8"	HOT				606 ²⁰⁷³ 106	AP606 ²⁰⁷³ AP106	APP606 ²⁰⁷³ APP106	XP606 ²⁰⁷³ XP105			
							605 ²⁰⁷³ 5245 ²⁴⁰⁵	AP605 ²⁰⁷³ AP5245 ²⁴⁰⁵	APP605 ²⁰⁷³ APP5245 ²⁴⁰⁵	XP605 ²⁰⁷³ XP5245 ²⁴⁰⁵			
							104 5144 ²⁴¹¹	AP104 AP5144 ²⁴¹¹	APP104 APP5144 ²⁴¹¹	XP104			
							103 5143 ²⁴¹¹ 5243 ²⁴⁰⁵	AP103 AP5143 ²⁴¹¹ AP5243 ²⁴⁰⁵	APP103 APP5243 ²⁴⁰⁵	XP103 XP5243 ²⁴⁰⁵			
				COLD									
15	14mm (Tapered Seat) .708" Half Thread	5/8"	HOT				2546 ²⁴¹⁰ 766	AP2546 ²⁴¹⁰ AP766	APP2546 ²⁴¹⁰				
							2545 ²⁴¹⁰ 765	AP2545 ²⁴¹⁰ AP765	APP2545 ²⁴¹⁰ APP765	XP5145 ²⁴⁰⁹			
							2544 ²⁴¹⁰ 764	AP2544 ²⁴¹⁰ AP764	APP2544 ²⁴¹⁰ APP764	XP5144 ²⁴⁰⁹			
				COLD			2543 ²⁴¹⁰	AP2543 ²⁴¹⁰					

Se reporter à l'index pour les remarques en français en bas de page. Ver el índice para las páginas de notas de pie de página en español.

²⁰⁷³ .060" Gap. ²³⁹⁹ Resistor. ²⁴⁰⁰ Power tip. ²⁴⁰³ Large gap. ²⁴⁰⁴ Special power tip. ²⁴⁰⁵ Special tip design. ²⁴⁰⁶ Long electrodes. ²⁴⁰⁷ Special plug for MAZDA rotary engine only. ²⁴⁰⁹ Full thread. ²⁴¹⁰ Special tip design for Ford. ²⁴¹¹ Long shell design. ²⁴¹⁷ Standard tip. ²⁴⁵⁶ Non-resistor. ²⁴⁵⁹ Longer upper end insulator.
⁷⁷³⁴ Xtreme Start. ⁷⁷³⁵ Xtreme Sport. ⁷⁸⁰⁶ Inductive suppressor.

Autolite® Spark Plug Heat Range Chart

Tableau des températures des bougies Autolite®

Tabla de grados térmicos de bujías Autolite®

	THREAD SIZE & REACH	HEX	HEAT RANGE	A	B	C	D	E	F	G	H	I	J
				STANDARD (NON-RESISTOR)	STANDARD (RESISTOR)	POWER TIP (NON-RESISTOR)	POWER TIP (RESISTOR)	PLATINUM	DOUBLE PLATINUM	XTREME PERFORMANCE	PREMIUM SMALL ENGINE	SHIELDED (RESISTOR)	SURFACE GAP
16	14mm (Tapered Seat) 1"	5/8"	HOT					AP5426 ²⁴⁰⁵	APP5426 ²⁴⁰⁵	XP5426 ²⁴⁰⁵			
									APP5344 ²⁴⁰⁸ APP5364 ²⁴⁰⁹	XP5364 ²⁴⁰⁹			
			COLD					AP5263 ^{2411, 2409}	APP5263 ^{2411, 2409}	XP5263 ^{2411, 2409}			
17	14mm (Gasket Seat) 1"	5/8"	HOT										
									APP5325	XP5325			
			COLD										
18	16mm (Tapered Seat) High Thread 1"	9/16"	HOT					HT2					
								HT15					
								HT1					
			COLD					HT0					
19	18mm .445"	1"	HOT										
			COLD	2695									
20	18mm 1/2"	7/8"	HOT		388							2227 ²³⁹⁹	
						3116						2226 ^{2399, 7806}	
					386							2225 ²³⁹⁹	
												2224 ^{2399, 7806}	
												2223 ^{2399, 7806}	
			COLD	373									
21	18mm (Tapered Seat) .460"	13/16"	HOT				46	AP46	APP46				
							45 5125 ²⁴¹¹	AP45 AP5125 ²⁴¹¹	APP45 APP5125 ²⁴¹¹				
			COLD		124			AP124					
22	18mm .968"	13/16"	HOT		824 ²⁴⁰²								
			COLD										
23	7/8"-18 5/8"	15/16"	HOT	3077									
			COLD	3076									
24	1/2" Pipe Thread 1"	7/8"	HOT	3095									
			COLD										

Se reporter à l'index pour les remarques en français en bas de page. Ver el índice para las páginas de notas de pie de página en español.

²³⁹⁹ Resistor. ²⁴⁰² .040 gap. ²⁴⁰⁵ Special tip design. ²⁴⁰⁸ Half thread. ²⁴⁰⁹ Full thread. ²⁴¹⁰ Special tip design for Ford. ²⁴¹¹ Long shell design. ⁷⁸⁰⁶ Inductive suppressor.